

newline

Connect. Create. Collaborate.

THE SUPERIOR, INTUITIVE INTERACTIVE DISPLAY EXPERIENCE



Superior
Image Quality



Seamless
Wireless Casting



Access to
the Cloud



Superior
Touch



Optical Bonding
Technology



Object
Recognition



Collaboration
Hub



Compatible with
all Devices

VN Series delivers the best visual and touch experience that captures your team's attention. Designed for an intuitive user experience, the more responsive touch technology brings you the most intuitive and smoothest writing quality imaginable.

With a vivid 4K resolution on an optically bonded screen, the VN Series provides a superior image quality that brings your presentations to life in stunning clarity. Optical bonding gives you an ultra-wide 178° viewing angle. No matter where you sit in the room, the image is vivid and clear. Object recognition technology lets the VN Series recognize when you are using a stylus or your finger, and switches between annotation modes based on how you are interacting with the display. Wirelessly cast to the display or access documents saved in Cloud storage, all with a seamless and easy to navigate user interface.

Add the multi-functional VN Series display to your conference room or huddle space and start communicating better and collaborating easier.

VN Series

VN Series

Model	VN65	VN75	VN86
Display			
Screen Size	65"	75"	86"
Display Area	56.2 x 31.6 in	65 x 38.3 in	74.6 x 42 in
Backlight	LED	LED	LED
Resolution	3840 x 2160 pixels	3840 x 2160 pixels	3840 x 2160 pixels
Display Ratio	16:9	16:9	16:9
Brightness	370nit	370nit	370nit
Display Colors	8 bit	8 bit	8 bit
Contrast Ratio	4000:1	4000:1	4000:1
Response Time	8 ms	8 ms	8 ms
Viewing Angle	178°	178°	178°
Lifetime Hours	50,000 hours	50,000 hours	50,000 hours
Speakers			
Position	Forward	Forward	Forward
Max Power Output	(2) 15W	(2) 15W	(2) 15W
Transmission Range	16.4 ft	16.4 ft	16.4 ft
Power			
Max Power Consumption	≤220W (Standby ≤0.5W)	≤350W (Standby ≤0.5W)	≤450W (Standby ≤0.5W)
Working Voltage	AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz
Touch			
Touch Surface	Optically bonded anti-glare glass	Optically bonded anti-glare glass	Optically bonded anti-glare glass
Touch Points	Up to 20 Points	Up to 20 Points	Up to 20 Points
Surface Hardness	>7H	>7H	>7H
Touch Sensor	Infrared Touch	Infrared Touch	Infrared Touch
Writing Tools	Stylus or Finger	Stylus or Finger	Stylus or Finger
Communication Interface	USB-A	USB-A	USB-A
Transportation/Storage			
Storage Temp/Humidity	14°F - 122°F / 20% - 80%	14°F - 122°F / 20% - 80%	14°F - 122°F / 20% - 80%
Working Temp/Humidity	10°F - 104°F / 20% - 80%	10°F - 104°F / 20% - 80%	10°F - 104°F / 20% - 80%
Mounting Options	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand
Outline Dimension	60.8 x 37 x 3.9 in	69.6 x 42 x 4.5 in	79.4 x 47.7 x 4.1 in
Weight	85.98 lbs	112.44 lbs	143.3 lbs
VESA	600x400	800x400	800x400
Embedded Operating System			
Chipset	ARM A53 x 4, 1.5 GHz	ARM A53 x 4, 1.5 GHz	ARM A53 x 4, 1.5 GHz
RAM	2GB	2GB	2GB
ROM	8GB	8GB	8GB
Android Version	5.0.1	5.0.1	5.0.1
Multimedia Files Supported	Image (JPEG, BMP, PNG); Video (MPEG1, MPEG2, MPEG4, H.264, H.265, MOV,, FLV); Audio (MP3, M4A, AAC)		
Ports			
Front Interface Inputs	HDMI 2.0 (4K@60Hz) x 2, HDMI 1.4 (4K@30Hz) x 1, USB (Touch) x 1, USB (Dynamic) x 2, DisplayPort x 1		
Rear AV Inputs	HDMI 2.0 (4K@60Hz) x 2, HDMI 1.4 (4K@30Hz) x 1, DisplayPort x 1, USB (Touch) x 4		
AV Outputs	HDMI out (Supports up to 4K@60Hz) x 1, Line Out x 1, SPDIF out x 1		
Other	USB (3.0) x 1, USB (2.0) x 2, RS232 x 1, RJ45 x 2, OPS Slots (4K@60Hz) x 1		